



Specifications:
 Current Rating:1.0A AC/DC
 Voltage Rating:30V AC/DC
 Contact Resistance:30m ohm. Max.
 Insulation Resistance:1,000M ohm. min.
 Withstanding Voltage:500V AC For One Minute
 Operating Temperature Range:-40°C ~ +105°C
 Material And Finish
 Insulator:PBT UL94V-0
 Contact:Phosphor Bronze
 Plating:Gold Plated on Contact Area,
 Tin Plated on Solder Tail.
 Shell:Brass,Nickel Plated

A	RELEASED	2017\03\17	杨磊	WK
LTR (版本)	DESCRIPTION (变更内容描述)	DATE (日期)	DWN (绘图)	APVD (核准)
REVISIONS (修订)				

THIS DRAWING IS A CONTROLLED DOCUMENT. (此图为宇亮公司受控文件)		DWN (绘图) 杨磊	2017\03\17	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO., LTD	
DIMENSIONS: (单位) mm		CHEK (审核) S. CHIEN	2017\03\17		
TOLERANCES UNLESS OTHERWISE SPECIFIED: (自由公差参照)		APVD (核准) Abel	2017\03\17	NAME (品名) USB AF 180 DIP TYPE	
THIRD ANGLE PROJECTION (第三视角)		PRODUCT SPEC (产品规范)	SIZE (尺寸) A4		
		WEIGHT (产品重量)	DRAWING No. (图号) YL001-018		
		CUSTOMER DRAWING (业务图)		SCALE (比例) 1 : 1	SHEET (张数) 1 OF 1